



Approved (SPF) Spray Foam Manufacturer and Type	Wet Film	Dry Film	Coverage Rate Per Gallon	IFTI ICC-ESR Evaluation report	IFTI IAPMO Evaluation report	SPF Manufacturer Evaluation Report
Icynene Classic 0.5 lb OC	4	3	400 sq. ft.	ESR-3702	ER-0499	ESR-1826
Icynene Classic Plus 0.7 lb. OC	4	3	400 sq.ft.	ESR-3702	ER-0499	ESR-1826
Icynene Classic Plus 0.7 lb. OC	14	9	New Spread Rate 115 sq.ft.	ESR-3702	ER-0499	ESR-1826
Icynene Classic Ultra 0.5 lb. OC	14	9	New Spread Rate 115 sq. ft.	ESR-3702	ER-0499	ESR-1826
Icynene Classic Ultra 0.5 lb. OC	4	3	400 sq.ft.	ESR-3702	ER-0499	ESR-1826
Icynene Classic Ultra Select 0.5 lb. OC	14	9	New Spread Rate 115 sq. ft.	ESR-3702	ER-0499	ESR-1826
Icynene Classic Ultra Select 0.5 lb. OC	4	3	400 sq.ft.	ESR-3702	ER-0499	ESR-1826
Icynene Classic® 0.5 lb. OC	14	9	New Spread Rate 115 sq. ft.	ESR-3702	ER-0499	ESR-1826
Icynene LD-C-50 No Mix	14	9	New Spread Rate 115 sq. ft	ESR-3702	ER-0499	CCRR 1123
Icynene LD-C-50 No Mix	4	3	400 sq. ft.	ESR-3702	ER-0499	CCRR 1123
Icynene M-D-C-200 2.0 lb CC	4	3	400 sq. ft.	ESR-3702	ER-0499	ESR-3199
Icynene MD-C-200 2 lb. CC	22	14	73 sq.ft.	ESR-3702	ER-0499	ESR-3199
Icynene Prime Gold	14	9	New Spread Rate 115 sq. ft	ESR-3702	ER-0499	ESR-4323
Icynene Prime Gold	4	3	400 sq. ft.	ESR-3702	ER-0499	ESR-4323
Icynene ProSeal 2 lb. CC	4	3	400 sq.ft.	ESR-3702	ER-0499	ESR-3500
Icynene ProSeal 2 lb. CC	14	9	New Spread Rate 115 sq.ft.	ESR-3702	ER-0499	ESR-3500
Icynene ProSeal HFO and HFO CW	14	9	New Spread Rate 115 sq. ft	ESR-3702	ER-0499	CCRR 1108
Icynene ProSeal LE	4	3	400 sq. ft.	ESR-3702	ER-0499	ESR-3500
Icynene ProSeal LE CC	14	9	New Spread Rate 115 sq.ft.	ESR-3702	ER-0499	ESR-3500

Approved Foam Testing Matrix For DC315

Building Code Fire Performance Requirements for SPF: The International Building Code (IBC) mandates that SPF be separated from the interior of the building by a prescriptive 15-minute thermal barrier, or other approved covering. **DC315 Carries IAPMO ER-0499 and ICC-ESR 3702 Evaluation Report** confirming DC315 provides an alternative thermal barrier assembly to the prescriptive thermal barrier requirements and all testing complies with the 2012 IBC Section 803.1.2 & 2603.10. 2012 IRC Section 316.6. 2015 IBC Section 803.2.1, 803.11, 2603.9 and 2015 IRC Section 316.6. DC 315 has also been tested as an ignition barrier under AC 377 Appendix X and meets the requirements of ICC-ES AC377 and AC456 Criteria.

Light Gold Cells are Ignition Barrier **Light Green Cells are Thermal Barrier**



Visit our Web site www.painttoprotect.com

[Application Guide](#) [Ventilation Guide](#) [Job Work Report](#) [Job Site Label](#) [Safety Data Sheets](#) [Master Specification](#) [Recommended Sprayer](#)