



Approved (SPF) Spray Foam Manufacturer and Type	Wet Film	Dry Film	Coverage Rate Per Gallon	IFTI ICC-ESR Evaluation report	IFTI IAPMO Evaluation report	SPF Manufacturer Evaluation Report
Demilec Agribalance 0.7 lb. OC	18	12	89 sq.ft.	<a href="#">ESR-3702</a>	<a href="#">ER-0499</a>	<a href="#">ESR-2600</a>
Demilec Agribalance 0.7 lb. OC	4	3	400 sq.ft.	<a href="#">ESR-3702</a>	<a href="#">ER-0499</a>	<a href="#">ESR-2600</a>
Demilec APX 0.5 lb. OC	20	13	80 sq.ft.	<a href="#">ESR-3702</a>	<a href="#">ER-0499</a>	<a href="#">ESR-3470</a>
Demilec APX 2.0	20	13	80	<a href="#">ESR-3702</a>	Update in Progress	<a href="#">ESR-3703</a>
Demilec Heatlok Arctic XT-w 2 lb. CC	14	9	New Spread Rate 115 sq.ft.	<a href="#">ESR-3702</a>	<a href="#">ER-0499</a>	<a href="#">ESR-3883</a>
Demilec Heatlok ECO	22	14	73 sq. ft.	<a href="#">ESR-3702</a>	Update in Progress	<a href="#">ESR-3198</a>
Demilec Heatlok ECO	4	3	400 sq. ft.	<a href="#">ESR-3702</a>	<a href="#">ER-0499</a>	<a href="#">ESR-3198</a>
Demilec Heatlok HFO High Lift 2 lb. CC	14	9	New Spread Rate 115 sq.ft.	<a href="#">ESR-3702</a>	<a href="#">ER-0499</a>	<a href="#">ESR-4073</a>
Demilec Heatlok HFO High Lift 2 lb. CC	4	3	400 sq.ft.	<a href="#">ESR-3702</a>	<a href="#">ER-0499</a>	<a href="#">ESR-4073</a>
Demilec Heatlok Soy 200+ 2 lb. CC	18	12	89 sq.ft.	<a href="#">ESR-3702</a>	<a href="#">ER-0499</a>	<a href="#">ESR-3210</a>
Demilec Heatlok XT-s 2 lb. CC	14	9	New Spread Rate 115 sq.ft.	<a href="#">ESR-3702</a>	<a href="#">ER-0499</a>	<a href="#">ESR-3824</a>
Demilec Heatlok® HFO PRO 2 lb. CC	18	12	89 sq.ft.	<a href="#">ESR-3702</a>	<a href="#">ER-0499</a>	<a href="#">ER-0565</a>
Demilec Sealection 500 0.5 lb. OC	4	3	400 sq.ft.	<a href="#">ESR-3702</a>	<a href="#">ER-0499</a>	<a href="#">ESR-1172</a>
Demilec Sealection 500 0.5 lb. OC	18	12	89 sq.ft.	<a href="#">ESR-3702</a>	<a href="#">ER-0499</a>	<a href="#">ESR-1172</a>
Demilec Sealection NM 0.5 lb. OC	18	12	89 sq. ft.	<a href="#">ESR-3702</a>	<a href="#">ER-0499</a>	<a href="#">ESR-2668</a>

**Approved Foam Testing Matrix For DC315**

**Building Code Fire Performance Requirements for SPF:** The International Building Code (IBC) mandates that SPF be separated from the interior of the building by a prescriptive 15-minute thermal barrier, or other approved covering. **DC315 Carries IAPMO ER-0499 and ICC-ESR 3702 Evaluation Report** confirming DC315 provides an alternative thermal barrier assembly to the prescriptive thermal barrier requirements and all testing complies with the 2012 IBC Section 803.1.2 & 2603.10, 2012 IRC Section 316.6, 2015 IBC Section 803.2.1, 803.11, 2603.9 and 2015 IRC Section 316.6. DC 315 has also been tested as an ignition barrier under AC 377 Appendix X and meets the requirements of ICC-ES AC377 and AC456 Criteria.

**Light Gold Cells are Ignition Barrier Light Green Cells are Thermal Barrier**



Visit our Web site [www.painttoprotect.com](http://www.painttoprotect.com)

[Application Guide Specification](#) [Ventilation Guide Recommended Sprayer](#) [Job Work Report](#) [Job Site Label](#) [Safety Data Sheets](#) [Master](#)