



Approved (SPF) Spray Foam Manufacturer and Type	Wet Film	Dry Film	Coverage Rate Per Gallon	IFTI ICC-ESR Evaluation report	IFTI IAPMO Evaluation report	SPF Manufacturer Evaluation Report
Patriot 200 2 lb. CC	14	9	New Spread Rate 115 sq.ft.	ESR-3702	ER-0499	ESR-4065
Patriot 200 2 lb. CC	4	3	400 sq.ft.	ESR-3702	ER-0499	ESR-4065
Patriot 500 0.5 lb. OC	20	13	80 sq.ft.	ESR-3702	ER-0499	ESR-4064
Patriot 500 0.5 lb. OC	4	3	400 sq.ft.	ESR-3702	ER-0499	ESR-4064
Patriot 500 HY 0.5 lb. OC	20	13	80 sq.ft.	ESR-3702	ER-0499	ESR-4064
Patriot 500 HY 0.5 lb. OC	4	3	400 sq.ft.	ESR-3702	ER-0499	ESR-4064

Approved Foam Testing Matrix For DC315

Building Code Fire Performance Requirements for SPF: The International Building Code (IBC) mandates that SPF be separated from the interior of the building by a prescriptive 15-minute thermal barrier, or other approved covering. DC315 Carries IAPMO [ER-0499](#) and [ICC-ESR 3702](#) Evaluation Report confirming DC315 provides an alternative thermal barrier assembly to the prescriptive thermal barrier requirements and all testing complies with the 2012 IBC Section 803.1.2 & 2603.10. 2012 IRC Section 316.6. 2015 IBC Section 803.2.1, 803.11, 2603.9 and 2015 IRC Section 316.6. DC 315 has also been tested as an ignition barrier under AC 377 Appendix X and meets the requirements of ICC-ES AC377 and AC456 Criteria.

Light Gold Cells are Ignition Barrier **Light Green Cells are Thermal Barrier**



Visit our Web site www.painttoprotect.com

- [Application Guide](#)
- [Ventilation Guide](#)
- [Job Work Report](#)
- [Job Site Label](#)
- [Safety Data Sheets](#)
- [Master Specification](#)
- [Recommended Sprayer](#)