



Approved (SPF) Spray Foam Manufacturer and Type	Wet Film	Dry Film	Coverage Rate Per Gallon	IFTI ICC-ESR Evaluation report	IFTI IAPMO Evaluation report	SPF Manufacturer Evaluation Report
Foam Supplies Inc. Ecostar CC	18	12	89 sq ft	Update in Progress	Update in Progress	CCRR-0388
Foam Supplies Inc. Genfoam OC	18	12	89 sq ft	Update in Progress	Update in Progress	CCRR-0389

Approved Foam Testing Matrix For DC315

Building Code Fire Performance Requirements for SPF: The International Building Code (IBC) mandates that SPF be separated from the interior of the building by a prescriptive 15-minute thermal barrier, or other approved covering. **DC315 Carries IAPMO ER-0499 and ICC-ESR 3702 Evaluation Report** confirming DC315 provides an alternative thermal barrier assembly to the prescriptive thermal barrier requirements and all testing complies with the 2012 IBC Section 803.1.2 & 2603.10, 2012 IRC Section 316.6, 2015 IBC Section 803.2.1, 803.11, 2603.9 and 2015 IRC Section 316.6. DC 315 has also been tested as an ignition barrier under AC 377 Appendix X and meets the requirements of ICC-ES AC377 and AC456 Criteria.

Light Gold Cells are Ignition Barrier **Light Green Cells are Thermal Barrier**



Visit our Web site www.painttoprotect.com

- [Application Guide Specification](#)
- [Ventilation Guide Recommended Sprayer](#)
- [Job Work Report](#)
- [Job Site Label](#)
- [Safety Data Sheets](#)
- [Master](#)